



## Material Safety Data Sheet

# Prop BH

**Code :** 03-003-0

**Prepared By :** ATT Laboratory

**Validation Date :** 01-Oct-2008

### 1. Chemical Product and Company Identification

**Trade Name** : Prop BH  
mix-Alcohol

**Chemical Name** : -

**Material Uses** : Solvent for paints industry, thinners and lacquers.

**Supplier** : **Asia Pacific Petrochemical Co., Ltd.**  
18 SCB Park Plaza Tower 2 (West), 21<sup>ST</sup> Floor,  
Zone C/2, Ratchadapisek Road, Chatuchak district,  
Chatuchak, Bangkok 10900  
**Telephone:** 02 9375615-20      **Facsimile:** 02 9375434  
[www.apcbkk.com](http://www.apcbkk.com)

**Emergency Contact** : 081 9212721 & 081 6203971

### 2. Composition/Information on Ingredients

#### Composition

Name	CAS No.	% By Weight
1.) n-Propanol	71-23-8	>60
2.) sec-Butyl alcohol	78-92-2	20-30
3.) Isobutyl alcohol	78-83-1	5.4
4.) n-Butanol	71-36-3	1.5

**UN No.** : 1987

### 3. Hazards Identification

**Safety Hazards** : Highly Flammable

**Human Health Hazards** : Irritating to eyes and skin. Harmful by inhalation and if swallowed.

**Environmental Hazards** : Not classified as dangerous under EU criteria.

#### 4. First Aid Measures

Inhalation	:	Remove to fresh air. If the victim has difficulty breathing or tightness of the chest, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
Skin Contact	:	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available.
Eye Contact	:	Immediately flush eyes with large amounts of water for at least 10 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment.
Ingestion	:	Immediately make victim drink plenty of water. Do not induce vomiting; Do not eat milk and castor oil, transport to nearest medical facility for additional treatment.

#### 5. Fire and Explosion Hazard Data

Flash Point	:	15 °C (Abel)
Flammable Limits	:	2.1 - 13.5 %V (n-Propanol)
Auto Ignition Temperature	:	343 °C (n-Butanol)
Chemical Reactivity	:	Stable under normal condition.
Materials to Avoid	:	Strong oxidizing agents, acids and strong alkalis.
Extinguishing Media	:	Water spray or fog, Dry chemical powder, Alcohol-resistant foam and Carbon dioxide.
Fire Fighting Additional Advice	:	Keep adjacent containers cool by spraying with water.
Protective Equipment	:	Wear full protective clothing and self-contained breathing apparatus.

#### 6. Accidental Release Measures

Protective Measures	:	<ul style="list-style-type: none"><li>• Observe all relevant local and international regulations.</li><li>• Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see chapter 8 this Material Safety Data Sheet. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.</li><li>• Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li></ul>
---------------------	---	---

### Clean-Up Methods

- ◆ Small spillage (< 200 LT) : Transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- ◆ large spillage (> 200 LT) : Transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

### Other Information

- : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## 7. Handling And Storage

### Handling

- : Avoid contact with skin, eyes, and clothing. Do not breathe vapours. Extinguish any naked flame. Remove ignition sources. Avoid sparks. Do not smoke. The vapour is heavier than air spreads along the ground and distant ignition is possible. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not use compressed air for filling, discharging, or handling operations. Handle and open container with care in well-ventilated area. Do not empty into drains.

### Storage

- : Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Bulk storage tanks should be diked (bunded). Keep away from aerosols, flammables, oxidizing agents, corrosives. Storage Temperature: Ambient.

### Product Transfer

- : Keep containers closed when not in use. Do not use compressed air for filling, discharging, or handling operations. If positive displacement pumps are used, these must be fitted with a non-integral pressure relief valve. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

### Recommended Materials

- : For containers, or container linings use mild steel, stainless steel.

### Additional Advice

- : Containers even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

## 8. Exposure Controls and Personal Protection

Exposure Standard	: Occupational Exposure Limits
	<b>n-Propanol</b> <ul style="list-style-type: none"> <li>• TLV-TWA = 200 ppm</li> <li>• TLV-STEL = 250 ppm</li> </ul>
	<b>sec-Butyl alcohol</b> <ul style="list-style-type: none"> <li>• TLV-TWA = 150 ppm (303 mg/m<sup>3</sup>)</li> </ul>
	<b>Isobutyl alcohol</b> <ul style="list-style-type: none"> <li>• TLV-TWA = 50 ppm (152 mg/m<sup>3</sup>)</li> </ul>
	<b>n-Butanol</b> <ul style="list-style-type: none"> <li>• TLV-TWA = 100 ppm</li> </ul>
Engineering Controls Workplace	: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective threshold limit value.
Respiratory Protection	: Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.
Hand Protection	: Butyl rubber gloves, Nature rubber gloves, Neoprene rubber gloves, Nitrile rubber gloves.
Eye Protection	: Chemical splash goggles (chemical monogoggles).
Other Protection	: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

## 9. Physical and Chemical Properties

Appearance	: Clear liquid.
Odour	: Specially odour.
Boiling Point (°C)	: 97.2 °C (n-Propanol) , weighted average: 98.81 °C
Melting Point (°C)	: -89.5 °C (n-Butanol) , weighted average: -121.1 °C
Vapour Pressure (mmHg)	: 14.9 mmHg @ 20 °C (n-Propanol). Weighted average: 12.9 mmHg @ 20 °C
Specific Gravity	: Weighted average: 0.81 @ 20 °C (ASTM D4052) (water = 1)
Density (g/cm <sup>3</sup> )	: 0.80 - 0.82 @ 20 °C (ASTM D4052)
Vapour Density	: 2.6 @ 20 °C (air = 1) (n-Butanol) , weighted average: 2.27 (air = 1)

Solubility in Water	:	Soluble complete @ 20 °C (ASTM D1722)
Evaporating Rate	:	1.3 (n-Butyl Acetate=1)
pH Value	:	No data available.

## 10. Stability and Reactivity

Stability	:	Stable under normal conditions.
Conditions to Avoid	:	Heat, flame, spark and other ignition sources.
Materials to Avoid	:	Strong oxidizing agents, acids and strong alkalis.
Hazardous Decomposition Products	:	Thermal decomposition is highly dependent on conditions. Carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation. May form explosive peroxides.
Hazardous Polymerisation	:	No.

## 11. Toxicological Information

### Acute Toxicity

#### n-Propanol

- ◆ LD<sub>50</sub> Acute oral toxicity : 1,870 mg/kg (rat)
- ◆ LD<sub>50</sub> Acute dermal toxicity : 4,060 mg/kg (rabbit)
- ◆ LC<sub>50</sub> Acute Inhalation Toxicity : 4,000 ppm 4 hours (rat)

Skin Irritation	:	Irritating to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
Eye Irritation	:	Irritating to eyes. Inflammation of the eye is characterized by redness, pain and itching.
Respiratory Irritation	:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Carcinogenicity	:	No data available.

## 12. Ecological Information

Mobility	:	Dissolves in water. If product enters soil, it will highly mobile and may contaminate groundwater.
Persistence / Degradability	:	Readily biodegradable.
Bio-accumulation	:	Not expected to bioaccumulate significantly

### 13. Disposal Considerations

- Material Disposal** : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
- Container Disposal** : Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send to drum recoverer or metal reclaimer
- Local Legislation** : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

### 14. Transport Information

#### Road/Rail Transport ADR/RID

- ◆ UN. Number : 1987
- ◆ Class/Item : 3
- ◆ Hazard Symbol : Flammable Liquid
- ◆ Proper Shipping Name : ALCOHOLS, N.O.S.
- ◆ Packing Group : II

#### Maritime Transport IMO

- ◆ UN. Number : 1987
- ◆ Class : 3.2
- ◆ Packing Group : II
- ◆ Hazard Symbol : Flammable Liquid
- ◆ Proper Shipping Name : ALCOHOLS, N.O.S.
- ◆ Marine Pollutant : No

#### Air Transport IATA/ICAO


- ◆ UN. Number : 1987
- ◆ Class : 3
- ◆ Packing Group : II
- ◆ Hazard Symbol : Flammable Liquid
- ◆ Proper Shipping Name : ALCOHOLS, N.O.S.

## 15. Regulatory Information

EC Label Name	:	Prop BH
EC Classification	:	Highly Flammable, Irritation.
EC Symbol	:	Xi F
EC Risk Phrases	:	R 11 Highly Flammable. R 36/37 Irritating to eyes and respiratory system. R 41 Risk of serious damage to eyes. R 67 Vapours may cause drowsiness and dizziness.
EC Safety Phrases	:	S 9 Keep container in a well-ventilated place. S 16 Keep away from sources of ignition – No smoking. S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 33 Take precautionary measures against static discharges. S 60 This material and its container must be disposed of as hazardous waste.

## 16. Other Information

National Fire Protection Association (USA) :



- Health
- Fire Hazard
- Reactivity
- Specific Hazard

MSDS Distribution : The information in this document should be made available to all who may handle the product.

Prepared By : Quality Control Department.  
Asia Pacific Petrochemical Co., Ltd.

### Disclaimer :

The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty of guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.

Revision 3 : October, 2008

