



ASIA PACIFIC PETROCHEMICAL CO., LTD.

165/14-16 Nirvana at Work Ramintra, Ramintra Road, Anusawari, Bang Khen, Bangkok, 10220

Tel. +66 2 1571555 Fax. +66 2 1571556

<http://www.apcbkk.com>

SALES SPECIFICATIONS

APC Product : Ethyl Acetate

APC Spec. No. : 04-001-0

Effective Date : 1 April 2018

Description

Ethyl acetate is a low-boiling ester with a pleasant non-residual odour, miscible with many organic solvents. It is an excellent solvent for cellulose esters.

Specification

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Purity	% m/m	GC	99.0 min
Colour (Pt-Cobalt)		ASTM D1209	10 max
Density @ 20 °C	g/ml	ASTM D4052	0.897 - 0.904
Water Content	% m/m	ASTM D1364	0.10 max
Distillation, IBP	°C	ASTM D1078	75.0 min
Distillation, DP	°C	ASTM D1078	78.0 max
Acidity as acetic acid	% m/m	ASTM D1613	0.01 max

Application

Ethyl acetate is widely used as a solvent in the surface coatings, adhesives, printing inks and other industries.

It is a solvent for nitrocellulose, acrylics, polyurethane, chlorinated rubber and vinyl.

Note : The Company reserves the right to change the information contained herein without notice.